BRUHATH BANGALORE MAHANAGARA PALIKE

NAME OF WORK: PROVIDING OPEN GYM AT YELAHANKA LAKE IN WARD NO. 01

MEASUREMENT SHEET

RA BILL NO FIRST AND PART

Name of Agency : Sri D.K.Nagaraja

Measurements recorded on 15.12.17.

Item no	From	Unit	nos	L (m)	B (m)	D (m)	Quantity	Remarks
1	2	3	4	5	6	7	8	9
12	Supply and Fixing of Bicycle. Metal: All tubular steel of 2.5mm thickness are galvanized and zinc dipped. Joints are Robotic welded. All welded joints are scalloped as necessary and welded to an approved MIG process. All welds are dressed off removing all sharp edges and burrs. Zinc Primer Paint is applied at all the welding points prior to finishing. All metal parts are powder coated using AKZO Nobel-Great Wall powder to the thickness of 80-120 microns. All metal parts are tested in our salt spray machine that uses a 5% NaCl solution in accordance to ISO7227 to speed up corrosion for 3000 hrs. Rubber: High quality grip rubber is used for the handles. Bearings: Maintenance-free ball bearings. Scope of delivery: 1 completely pre-assembled equipment modules. Maintenance: Maintain according to EN 16630 and the maintenance guide. Safety: All products must be tested and certified to meet EN16630 safety standards only by a reputed notified international certifying agency such as IPEMA, TUV, CPSC, or SGS. The GS Mark- EN16630 Certificates must be in the name of tendering party and not any 3rd party. Size_L x W x H): 1000 x 498 x 1290 mm. Weight: 51.5 Kg Safety Area: 3400 x 3498 mm Capacity_1 Persons.							
		No						
		Checked.	1x2				2	
						Total Qty	2	

15/12

E.E. (Project)

Contractor

Asst. Engineer

Asst. Executive Engineer
Project Division
Yelahanka Zone
Bangalore

BRUHATH BANGALORE MAHANAGARA PALIKE

NAME OF WORK: PROVIDING OPEN GYM AT YELAHANKA LAKE IN WARD NO. 01

MEASUREMENT SHEET

RA BILL NO FIRST AND PART

Name of Agency : Sri D.K.Nagaraja

Measurements recorded on 15.12.17.

Item no	From	Unit	nos	L (m)	B (m)	D (m)	Quantity	Remarks
1	2	3	4	5	6	7	8	9
13	Supply and fixing of Seated Chest Press. Metal: All tubular steel of 2.5mm thickness are galvanized and zinc dipped. Joints are Robotic welded. All welded joints are scalloped as necessary and welded to an approved MIG process. All welds are dressed off removing all sharp edges and burrs. Zinc Primer Paint is applied at all the welding points prior to finishing. All metal parts are powder coated using AKZO Nobel-Great Wall powder to the thickness of 80-120 microns. All metal parts are tested in our salt spray machine that uses a 5% NaCl solution in accordance to ISO7227 to speed up corrosion for 3000 hrs. Rubber: High quality grip rubber is used for the handles. Bearings: Maintenance-free ball bearings. Scope of delivery: 1 completely pre-assembled equipment modules. Maintenance: Maintain according to EN 16630 and the maintenance guide. Safety: All products must be tested and certified to meet EN16630 safety standards with GS test mark. The EN 16630 certificates must be issued by a reputed notified international certifying agency such as IPEMA, TUV, CPSC, or SGS only. The GS Mark- EN16630 Certificates must be in the name of tendering party and not any 3rd party. All products must clearly display the GS mark as has been issued in the EN16630 safety certificates. All products must carry a GS mark on it.. Size_L x W x H): 1955 x 733 x 2058 mm. Weight: 86.6 Kg Safety Area: 5545 x 4470 mm Capacity_2 Persons.							
		No						
		1x2					2	
						Total Qty	2	

Checked.

15/12

E.E. (Project)

Contractor

Asst. Engineer

Asst. Executive Engineer
Project Division
Yelahanka Zone
Bangalore

BRUHATH BANGALORE MAHANAGARA PALIKE

NAME OF WORK: PROVIDING OPEN GYM AT YELAHANKA LAKE IN WARD NO. 01

MEASUREMENT SHEET

RA BILL NO FIRST AND PART

Name of Agency : Sri D.K.Nagaraja

Measurements recorded on 15.12.17 .

Item no	From	Unit	nos	L (m)	B (m)	D (m)	Quantity	Remarks
1	2	3	4	5	6	7	8	9
14	Supply and fixing of Self Weighted Rower. Metal: All tubular steel of 2.5mm thickness are galvanized and zinc dipped. Joints are Robotic welded. All welded joints are scalloped as necessary and welded to an approved MIG process. All welds are dressed off removing all sharp edges and burrs. Zinc Primer Paint is applied at all the welding points prior to finishing. All metal parts are powder coated using AKZO Nobel-Great Wall powder to the thickness of 80-120 microns. All metal parts are tested in our salt spray machine that uses a 5% NaCl solution in accordance to ISO7227 to speed up corrosion for 3000 hrs. Colour RAL 5019 Blue and RAL 1014 Beige Rubber: High quality grip rubber is used for the handles. Bearings: Maintenance-free ball bearings. Scope of delivery: 1 completely pre-assembled equipment modules. Maintain according to EN 16630 and the maintenance guide. Safety: All products must be tested and certified to meet EN16630 safety standards only by a reputed notified international certifying agency such as IPEMA, TUV, CPSC, or SGS. The GS Mark-EN16630 Certificates must be in the name of tendering party and not any 3rd party. All products must carry a GS mark on it.. Size_L x W x H): 1390 x 805 x 1100 mm. Weight: 42.4 Kg Safety Area: 3790 x 3205 mm Capacity_1 Person.							
		No						
			1x2				2	1
		Checked.			Total Qty		2	1

15/12

E.E. (Project)

Contractor

Asst. Engineer

Asst. Executive Engineer
Project Division
Yelahanka Zone

Asst. Executive Engineer

(15)

BRUHATH BANGALORE MAHANAGARA PALIKE

NAME OF WORK: PROVIDING OPEN GYM AT YELAHANKA LAKE IN WARD NO. 01

MEASUREMENT SHEET

RA BILL NO FIRST AND PART

Name of Agency : Sri D.K.Nagaraja

Measurements recorded on 15.12.17.

Item no	From	Unit	nos	L (m)	B (m)	D (m)	Quantity	Remarks
1	2	3	4	5	6	7	8	9
15	Supply and Fixing of HD Sit Up Station. Metal: All tubular steel of 2.5mm thickness are galvanized and zinc dipped. Joints are Robotic welded. All welded joints are scalloped as necessary and welded to an approved MIG process. All welds are dressed off removing all sharp edges and burrs. Zinc Primer Paint is applied at all the welding points prior to finishing. All metal parts are powder coated using AKZO Nobel-Great Wall powder to the thickness of 80-120 microns. All metal parts are tested in our salt spray machine that uses a 5% NaCl solution in accordance to ISO7227 to speed up corrosion for 3000 hrs. Rubber: High quality grip rubber is used for the handles. Bearings: Maintenance-free ball bearings. Scope of delivery: 1 completely pre-assembled equipment modules. Maintenance: Maintain according to EN 16630 and the maintenance guide. Safety: All products must be tested and certified to meet EN16630 safety standards with GS test mark. The EN 16630 certificates must be issued by a reputed notified international certifying agency such as IPEMA, TUV, CPSC, or SGS only. The GS Mark- EN16630 Certificates must be in the name of tendering party and not any 3rd party. . All products must clearly display the GS mark as has been issued in the EN16630 safety certificates. Size_L x W x H): 1412 x 1366 x 650 mm. Weight: 42.6 Kg Safety Area: 4462 x 4078 mm Capacity_2 Persons.							
		No						
			1x2				2	
		Checked			Total Qty		2	

15/12

E.E. (Project)

contractor

Asst. Engineer

Asst. Executive Engineer
Project Division
Yelahanka Zone
Bangalore

Asst. Executive Engineer

BRUHATH BANGALORE MAHANAGARA PALIKE

NAME OF WORK: PROVIDING OPEN GYM AT YELAHANKA LAKE IN WARD NO. 01

MEASUREMENT SHEET

RA BILL NO FIRST AND PART

Name of Agency : Sri D.K.Nagaraja

Measurements recorded on 15.12.17.

Item no	From	Unit	nos	L (m)	B (m)	D (m)	Quantity	Remarks
1	2	3	4	5	6	7	8	9
16	Supply and fixing of HD Squat Pushing. Metal: All tubular steel of 2.5mm thickness are galvanized and zinc dipped. Joints are Robotic welded. All welded joints are scalloped as necessary and welded to an approved MIG process. All welds are dressed off removing all sharp edges and burrs. Zinc Primer Paint is applied at all the welding points prior to finishing. All metal parts are powder coated using AKZO Nobel-Great Wall powder to the thickness of 80-120 microns. All metal parts are tested in our salt spray machine that uses a 5% NaCl solution in accordance to ISO7227 to speed up corrosion for 3000 hrs. Rubber: High quality grip rubber is used for the handles. Bearings: Maintenance-free ball bearings. Scope of delivery: 1 completely pre-assembled equipment modules.Maintenance: Maintain according to EN 16630 and the maintenance guide. Safety: All products must be tested and certified to meet EN16630 safety standards with GS test mark. The EN 16630 certificates must be issued by a reputed notified international certifying agency such as IPEMA, TUV, CPSC, or SGS only. The GS Mark- EN16630 Certificates must be in the name of tendering party and not any 3rd party. All products must clearly display the GS mark as has been issued in the EN16630 safety certificates.SizeL x W x H): 2270 x 635 x 1640 mm. Weight: 60.2Kg. Safety Area: 5300 * 3685mm. Capacity 2 Persons							
		No						
			1x2				2	
						Total Qty	2	

Checked.

15/12

E.E. (Project)

contractor

Asst. Engineer

Asst. Executive Engineer
Project Division
Yelahanka Zone
Bangalore

Asst. Executive Engineer